Simulated Space Environmental Effects on Thin Film Solar Array Components

Miria M. Finckenor

Dr. John Carr

Michael SanSoucie

Darren Boyd

NASA Marshall Space Flight Center, Huntsville, AL 35812 USA

Brandon Phillips

ESSSA, Huntsville, AL USA,

Applied Space Environments Conference

Huntsville, AL

May 2017

Simulated Space Environmental Effects on Thin Film Solar Array Components

- **Background**
- **Solar Array Materials**
- **Simulated Space Environment Exposures**
  - **Atomic Oxygen**
  - **Ultraviolet Radiation**
  - **Electron Radiation**
  - **Proton Radiation**
  - **Thermal Cycling**
- **Summary**

Simulated Space Environmental Effects on Thin Film Solar Array Components

- **Lightweight Integrated Solar Array and Transceiver (LISA-T)**
  - **Deployable solar array**
  - **Can provide over a hundred watts of power yet stow into less than a standard one-unit (1U) CubeSat, or a volume of less than 4 inches x 4 inches x 4 inches**
  - **Flexible solar cells do not allow for standard coverglass protection from the space environment**
  - **Candidate solar cells and protective thin films tested in space environment simulations**





Simulated Space Environmental Effects on Thin Film Solar Array Components

- **Solar Cells**
  - **Inverted metamorphic multi-junction (IMM)**
    - **High performance, higher cost, modestly lightweight, extremely thin**
  - **Copper indium gallium (di)selenide (CIGS)**
    - **Low cost, lower efficiency**
    - **Less than half the weight of the IMM cell but twice the thickness**
  - **Single junction GaAs cells**
    - **Medium option in cost and efficiency**
- **Solar cell performance evaluated by power curves, optical properties, mass loss**

Simulated Space Environmental Effects on Thin Film Solar Array Components

- **Thin Films**
  - **CORIN**
  - **CORIN with cerium oxide**
  - **Optinox**
  - **Optinox with cerium oxide**
- **Applied to solar cells or exposed separately**
- **Performance evaluated by transmission measurements, mass loss**

Simulated Space Environmental Effects on Thin Film Solar Array Components

- **Atomic Oxygen**
  - **Atomic Oxygen Beam Facility**
  - **5 eV neutral oxygen atoms with concurrent vacuum UV radiation**
  - **Iterations up to 2.5 x 10^{21} atoms/cm^2 fluence**
  - **One bare and one CORIN-coated IMM solar cell**
  - **All candidate thin films plus nitinol wire**



Simulated Space Environmental Effects on Thin Film Solar Array Components

- **Atomic Oxygen Results**
  - **Bare Solar Cell**
    - **Mass loss of 1.3%**
    - **97.6% power retention**
  - **CORIN coated solar cell**
    - **Mass loss of 1.9%**
    - **103.6% power retention due to surface texturing and slight decrease in reflectance**



  - **Optinox film heavily eroded**
  - **CORIN formed self-passivating layer in AO**
  - **Nitinol wire had slight mass loss, no performance changes**

Simulated Space Environmental Effects on Thin Film Solar Array Components

- **Ultraviolet Radiation**
  - **Solar Simulator with xenon arc lamp**
  - **IMM and CIGS cells**
    - **Bare**
    - **Coated with Optinox**
    - **Coated with CORIN**
    - **Coated with CORIN with cerium oxide**
  - **Iterations up to 2,000 equivalent sun hours**



Simulated Space Environmental Effects on Thin Film Solar Array Components

- **Ultraviolet Radiation Results**
  - **Bare IMM**
    - **98.5% power retention**
  - **Coated IMM**
    - **80.8% power retention for CORIN, slightly better with addition of ceria**
    - **85.5% power retention for Optinox**
  - **Bare CIGS**
    - **Degraded open circuit voltage, 70% power retention at best**
  - **Coated CIGS**
    - **86.5% power retention for CORIN, 91.6% with addition of ceria**
    - **73.4% power retention for Optinox**

Simulated Space Environmental Effects on Thin Film Solar Array Components

- **Electron Radiation**
  - **Combined Environmental Effects Facility with Pelletron accelerator**
  - **1 MeV electrons**
  - **IMM, CIGS, and single junction GaAs cells**
    - **Bare**
    - **Coated with Optinox**
    - **Coated with CORIN**
    - **Coated with CORIN with cerium oxide**
  - **CORIN and CORIN with ceria thin films also exposed**
  - **Iterations from 3 x 10^{13} up to 5 x 10^{15} e-/cm^2**

Simulated Space Environmental Effects on Thin Film Solar Array Components

- **Electron Radiation Results**
  - **Coatings had little effect on solar cell durability**
  - **IMM**
    - **Slightly degraded after 1 x 10^{14} e-/cm^2**
  - **CIGS**
    - **Maintained power retention through all exposures**
  - **Bare single junction GaAs**
    - **Significant degradation**
  - **No significant change in transmission for either type of film**

Simulated Space Environmental Effects on Thin Film Solar Array Components

- **Proton Radiation**
  - **Combined Environmental Effects Facility with Pelletron accelerator**
  - **IMM and CIGS cells**
    - **Bare**
    - **Coated with Optinox (IMM only)**
    - **Coated with CORIN**
    - **Coated with CORIN with cerium oxide**
  - **50 keV iterations from 7 x 10^{10} up to 1 x 10^{15} p+/cm^2**
  - **100 keV, 500 keV, 700 keV 1 x 10^{13} p+/cm^2**

Simulated Space Environmental Effects on Thin Film Solar Array Components

- **Proton Radiation Results**
  - **IMM**
    - **Bare cells degraded after 1 x 10^{12} p+/cm^2 at 50 keV**
    - **Coated cells started degrading at 1 x 10^{15} p+/cm^2 at 50 keV**
    - **Coated cells maintained power retention through higher energy exposures**
  - **CIGS**
    - **Bare cells degraded with 50 keV exposure**
    - **Coated cells maintained power retention through all exposures**

Simulated Space Environmental Effects on Thin Film Solar Array Components

- **Thermal Cycling**
  - **Associate Engineering rapid thermal shock chamber**
  - **IMM cells**
    - **Bare**
    - **Coated with CORIN**
  - **CIGS cells**
    - **Bare**
    - **Coated with CORIN**
    - **Coated with CORIN plus anti-reflectance**
  - **CIGS and IMM sub-coupons with solar array boom elements were cycled at least 35 times and in some cases up to 100 times.**
  - **Temperatures from -55 to +125 °C**



Simulated Space Environmental Effects on Thin Film Solar Array Components

- **Thermal Cycling Results**
  - **IMM**
    - **Some delamination of coating**
  - **CIGS**
    - **CORIN-coated cells performed well**
    - **AR coating delaminated**
    - **AR process has been improved but not yet tested**
  - **IMM and CIGS sub-coupons with boom elements**
    - **Both had one cell drop out for power loss**
    - **Test will be repeated to determine if power loss due to handling or thermal cycling**



Simulated Space Environmental Effects on Thin Film Solar Array Components

- **Summary**
  - **CORIN and CORIN with cerium oxide show promise as protective coatings for both IMM and CIGS solar cells.**
  - **CORIN was particularly effective in protection from AO and proton radiation damage.**
  - **Optinox shows promise as a protective coating for the IMM solar cells outside of the AO environment.**

- **Acknowledgements**
  - **Special thanks to:**
    - **Space Technology Mission Directorate (STMD) Early Career Initiative for funding this effort**
    - **Curtis Bahr for lab support and Joey Norwood for assistance during AO testing**
    - **Nexolve – partner in LISA-T program, providing coated solar cells and thin film samples**